




BPS-80

Suction water level down to 3 mm




Model	Output		Outlet		Pass Solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	2M	2.5M	3M	3.5M			
BPS-80	1/10	80	20	3/4"	3	40	38	35	30	22	12	4	136 x 136 x 232	2.3
BPS-80A	1/10	80	20	3/4"	3	40	38	35	30	22	12	4	136 x 136 x 232	2.8

Remarks: Model with "A" is equipped with float switch.



BPS-200/300/400

Multi-function Longevity Portability Pumps




Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	2M	4M	6M	8M			
BPS-200	1/4	200	32	1-1/4"	5	140	135	130	100	40	-	7	155 x 140 x 255	4.2
BPS-300	1/3	300	40	1-1/2"	5	180	170	160	120	65	-	8	196 x 160 x 370	6.6
BPS-400	1/2	400	50	2"	5	220	210	200	155	100	35	9	196 x 160 x 370	7.6

Remarks: Model with "A" is equipped with float switch. Model with "V" is equipped with vertical switch.



BPS-100

Suction water level down to 3mm




Model	Output		Outlet		Pass Solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	3M	4M	5M	6M			
BPS-100	1/6	100	25	1"	3	70	68	54	41	25	8	6.5	155 x 140 x 240	3.1
BPS-100A	1/6	100	25	1"	3	70	68	54	41	25	8	6.5	155 x 140 x 240	3.3
BPS-100V	1/6	100	25	1"	3	70	68	54	41	25	8	6.5	155 x 140 x 240	3.3

Remarks: Model with "A" is equipped with float switch. Model with "V" is equipped with vertical switch.



BPS-180M BPS-200M





Model	Output		Outlet		Pass solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	2M	3M	4M	5M			
BPS-180M	1/6	120	32	1-1/4"	5	120	115	105	80	48	15	5.5	189 x 148 x 227	3
BPS-200M	1/4	180	32	1-1/4"	5	180	170	160	130	100	65	6.5	189 x 148 x 257	3.6

Remarks: Model with "A" is equipped with float switch. Model with "V" is equipped with vertical switch.



SM Series

Automatic ON/OFF control Without Float Switch



Model	Output		Outlet		Pass Solid Dia(mm)	Max Flow(LPM)	LPM Flow @ Head					Max Head(M)	Dimension L x W x H (mm)	Weight Kg
	HP	W	mm	Inch			1.5M	3M	4.5M	6M	7.5M			
SM-100	1/6	120	25	1"	3	70	65	55	30	-	6	155 x 140 x 240	3.5	
SM-200	1/4	200	32	1-1/4"	3	140	130	100	65	25	-	7	155 x 140 x 255	4.5
SM-300	1/3	300	40	1-1/2"	3	180	170	150	125	80	25	8	196 x 160 x 370	6.8
SM-400	1/2	400	50	2"	3	220	210	190	155	120	75	10	196 x 160 x 370	8.5

Remarks: Optional for lower strainer on SM100 & 200.